IN THE CLAIMS

Please amend the claims as follows:

Claim 1 (Currently Amended): In a belt device passed over a plurality of rollers one of which is adjacent to a heat source, a temperature of part of a belt moving in the vicinity of said heat source varies little relative to a temperature of the other part of said belt, wherein said roller adjacent to the heat source comprises metallic and non-metallic portions, said non-metallic portions having a lower thermal conductivity than metal said belt is passed over said plurality of rollers, and one of said plurality of rollers adjacent to the heat source is configured to obstruct heat transfer to said belt.

Claim 2 (Original): The belt device as claimed in claim 1, wherein said belt is passed over said plurality of rollers, and one of said plurality of rollers adjacent to the heat source is configured to obstruct heat transfer to said belt.

Claim 3 (Cancelled)

Claim 4 (Original): The belt device as claimed in claim 1, wherein said roller adjacent to the heat source comprises belt passing portions over which said belt is passed in an axial direction of said roller and heat non-conductive portions not conducting heat.

Claim 5 (Original): The belt device as claimed in claim 4, wherein said heat non-conductive portions are lower in thermal conductivity than metal.

Claim 6 (Original): The belt device as claimed in claim 4, wherein said belt passing portions comprise metallic surfaces capable of serving as optical reflecting surfaces.

Claim 7 (Original): The belt device as claimed in claim 4, wherein said heat non-

conductive portions each comprise a flexible member capable of contacting said belt.

Claim 8 (Original): The belt device as claimed in claim 4, wherein said heat non-

conductive portions each comprise bristles implanted and capable of contacting said belt.

Claim 9 (Original): The belt device as claimed in claim 8, wherein said bristles have

a density of 1,000/cm² to 50,000/cm².

Claim 10 (Original): The belt device as claimed in claim 8, wherein said bristles

have a height equal to an outside diameter of said belt passing portions or great enough for

said bristles to contact said belt.

Claim 11 (Original): The belt device as claimed in claim 4, wherein said heat non-

conductive portions are formed at positions other than end portions of said roller in an axial

direction of said roller.

Claim 12 (Original): The belt device as claimed in claim 4, wherein said heat non-

conductive portions are formed of an electrically conductive material.

Claim 13 (Original): The belt device as claimed in claim 12, wherein said heat non-

conductive portions have a specific resistance of $10^{-3} \Omega \cdot \text{cm}$ to $10^{-1} \Omega \cdot \text{cm}$.

Claim 14 (Currently Amended): In an image forming apparatus using a belt device, said belt device is passed over a plurality of rollers one of which is adjacent to a heat source, and a temperature of part of a belt moving in the vicinity of said heat source varies little relative to a temperature of the other part of said belt, wherein said roller adjacent to the heat source comprises metallic and non-metallic portions, said non-metallic portions having a lower thermal conductivity than metal said belt is passed over said plurality of rollers, and one of said plurality of rollers adjacent to the heat source is configured to obstruct heat transfer to said belt.

Claim 15 (Original): The apparatus as claimed in claim 14, wherein said belt constitutes an image transfer body, and one of said rollers over which said belt is passed is adjacent to a fixing unit including a heat source.

Claim 16 (Original): The apparatus as claimed in claim 15, wherein a plurality of image carriers are arranged side by side and allow respective latent images corresponding to different colors to be formed thereon and developed by toners complementary in color to said latent images to thereby form corresponding toner images, said belt, conveying a sheet electrostatically adhering to said belt, moves via said plurality of image carriers to thereby cause said toner images to be sequentially transferred to said sheet one above the other and conveys said sheet further to a fixing unit.

Claim 17 (Original): The apparatus as claimed in claim 14, wherein said belt constitutes a photoconductive element, and one of rollers over which said belt is passed is adjacent to the fixing device including a heat source.

Claim 18 (Original): In a belt device comprising a belt passed over a plurality of rollers and capable of moving said belt via said plurality of rollers, bristles are implanted on a circumferential surface of any one of said plurality of rollers except for belt passing portions over which said belt is passed, and said bristles are arranged in an axial direction of said roller and each are inclined relative to a line tangential to said circumferential surface.

Claim 19 (Original): The belt device as claimed in claim 18, wherein said bristles are implanted on at least one roller located at a position where a temperature is high in a temperature distribution in a direction of movement of said belt.

Claim 20 (Original): The belt device as claimed in claim 18, wherein said bristles are inclined in a direction in which said bristles fall down rearward in a direction of rotation of said roller.

Claim 21 (Original): The belt device as claimed in claim 18, wherein said bristles are inclined by a same angle.

Claim 22 (Original): The belt device as claimed in claim 18, wherein a distance between an axis of said roller and tips of said bristles differs, in the axial direction of said roller, from positions adjoining said belt passing portions to the other portions.

Claim 23 (Original): The belt device as claimed in claim 22, wherein the tips of said bristles at the positions adjacent to said belt passing portions are positioned radially outward of said belt passing portions.

Claim 24 (Original): The belt device as claimed in claim 22, wherein said bristles

have a same length as each other.

Claim 25 (Original): The belt device as claimed in claim 18, wherein positions of

said roller, adjoining said belt passing portions in the axial direction of said roller, have an

outside diameter smaller than said belt passing portions, but larger than the other positions.

Claim 26 (Original): The belt device as claimed in claim 18, wherein said bristles are

implanted in a range of said roller other than end portions in the axial direction of said roller.

Claim 27 (Original): The belt device as claimed in claim 18, wherein said bristles are

lower in thermal conductivity than a material forming said roller.

Claim 28 (Original): The belt device as claimed in claim 18, wherein said bristles are

electrically conductive.

Claim 29 (Original): The belt device as claimed in claim 18, wherein said bristles are

formed of a material having a specific resistance of $10^{-3} \ \Omega \cdot \text{cm}^2$ to $10^{-1} \ \Omega \cdot \text{cm}^2$.

Claim 30 (Original): The belt device as claimed in claim 18, wherein said bristles

have a density of 1,0001cm² to 50,0001cm².

Claim 31 (Original): The belt device as claimed in claim 18, wherein said belt

passing portions of said roller comprise metallic surfaces capable of serving as optical

reflecting surfaces.

Claim 32 (Original): In an image forming apparatus using a belt device, said belt

device comprises a belt passed over a plurality of rollers and is capable of moving said belt

via said plurality of rollers, bristles are implanted on a circumferential surface of any one of

said plurality of rollers except for belt passing portions over which said belt is passed, and

said bristles are arranged in an axial direction of said roller and each are inclined relative to a

line tangential to said circumferential surface.

Claim 33 (Original): The apparatus as claimed in claim 32, wherein said belt

constitutes an image transfer body, and one of said rollers over which said belt is passed is

adjacent to a fixing device including a heat source.

Claim 34 (Original): The apparatus as claimed in claim 32, wherein said belt

constitutes an image carrier, and one of said rollers over which said belt is passed is adjacent

to a fixing device including a heat source.

Claim 35 (Original): The apparatus as claimed in claim 32, wherein said belt is used

for a color image forming process capable of forming a plurality of images of different

colors.

Claim 36 (Original): The apparatus as claimed in claim 35, wherein said belt is used

for a plurality of tandem image forming sections arranged side by side and constitutes an

image transfer belt having a surface movable via said plurality of tandem image forming

sections, whereby images of different colors formed by said image forming sections are

transferred to said surface of said image transfer belt or a recording sheet, electrostatically

adhering to said belt, one above the other.

Claim 37 (Previously Presented): In a belt device passed over a plurality of rollers

one of which is adjacent to a heat source, a temperature of part of a belt, moving in the

vicinity of said heat source, is made identical with a temperature of the other part in a short

period of time, the temperature of said roller adjacent to the heat roller drops in a shorter

period of time than a solid metallic roller, and when said roller adjacent to the heat roller

comprises a hollow roller, at least one radially extending rib is positioned inside said hollow

roller.

Claim 38 (Original): The belt device as claimed in claim 37, wherein said belt is

passed over a plurality of rollers, one of said plurality of rollers adjacent to the heat source

radiates a greater amount of heat than the other rollers.

Claim 39 (Cancelled)

Claim 40 (Currently Amended): The belt device as claimed in claim 39 37, wherein

said roller adjacent to the heat source comprises a hollow roller.

Claim 41 (Currently Amended): The belt device as claimed in claim 39 37, wherein

when said roller adjacent the heat roller comprises a hollow roller, a wall thickness of said

roller is 5 mm or below.

Claim 42 (Cancelled)

Claim 43 (Currently Amended): The belt device as claimed in claim 39 37, wherein said roller adjacent to the heat roller is formed of a good conductor selected from at least aluminum, stainless steel (SUS) and steel.

Claim 44 (Previously Presented): In an image forming apparatus using a belt device, said belt device is passed over a plurality of rollers one of which is adjacent to a heat source, and a temperature of part of a belt, moving in the vicinity of said heat source, is made identical with a temperature of the other part in a short period of time, the sheet starts being conveyed toward an image transfer position after the temperature of said belt has been made equal at a position where said belt moves in the vicinity of the heat source and the other positions.

Claim 45 (Original): The apparatus as claimed in claim 44, wherein said belt constitutes an image transfer body, and one of said rollers over which said belt is passed is adjacent to a fixing unit including a heat source.

Claim 46 (Original): The apparatus as claimed in claim 45, wherein said belt constitutes a photoconductive element, and one of rollers over which said belt is passed is adjacent to the fixing device including a heat source.

Claim 47 (Original): The apparatus as claimed in claim 45, wherein a plurality of image carriers are arranged side by side and allow respective latent images corresponding to different colors to be formed thereon and developed by toners complementary in color to said latent images to thereby form corresponding toner images, said belt, conveying a sheet

electrostatically adhered to said belt, moves via said plurality of image carriers to thereby

cause said toner images to be sequentially transferred to said belt one above the other and

conveys said sheet further to a fixing unit.

Claim 48 (Cancelled)

Claim 49 (Original): The apparatus as claimed in claim 44, wherein control for

correcting a shift of an image position starts being executed after the temperature of said belt

has been made equal at a position where said belt moves in the vicinity of the heat source and

the other positions.

Claim 50 (Previously Presented): In an image forming apparatus using a belt device,

said belt device is passed over a plurality of rollers one of which is adjacent to a heat source,

and a temperature of part of a belt, moving in the vicinity of said heat source, is made

identical with a temperature of the other part in a short period of time, wherein control for

correcting a shift of an image position starts being executed after the temperature of said belt

has been made equal at a position where said belt moves in the vicinity of the heat source and

the other positions.

Claim 51 (Previously Presented): The apparatus as claimed in claim 50, wherein said

belt constitutes an image transfer body, and one of said rollers over which said belt is passed

is adjacent to a fixing unit including a heat source.

Claim 52 (Previously Presented): The apparatus as claimed in claim 51, wherein said belt constitutes a photoconductive element, and one of rollers over which said belt is passed is adjacent to the fixing device including a heat source.

Claim 53 (Previously Presented): The apparatus as claimed in claim 51, wherein a plurality of image carriers are arranged side by side and allow respective latent images corresponding to different colors to be formed thereon and developed by toners complementary in color to said latent images to thereby form corresponding toner images, said belt, conveying a sheet electrostatically adhered to said belt, moves via said plurality of image carriers to thereby cause said toner images to be sequentially transferred to said belt one above the other and conveys said sheet further to a fixing unit.

Claim 54 (Previously Presented) The apparatus as claimed in claim 50, wherein the sheet starts being conveyed toward an image transfer position after the temperature of said belt has been made equal at a position where said belt moves in the vicinity of the heat source and the other positions.

Claim 55 (Previously Presented) The apparatus as claimed in claim 51, wherein a plurality of image carriers are arranged side by side and allow respective latent images corresponding to different colors to be transferred, sequentially, to an intermediate image transfer body and then to a sheet.